

PU HARDENER

TH0801/00

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : PU HARDENER  
**Product code** : TH0801/00

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Paint or paint related material.  
: Industrial use only.

### 1.3 Details of the supplier of the safety data sheet

SHERWIN-WILLIAMS Italy S.r.l.  
Via del Fiffo, 12 - 40065 Pianoro (BO)  
Italia - C.P. 18  
Cod. Fisc. e Reg. Impr. Bo 08866930152  
**e-mail address of person responsible for this SDS** : regulatory.SWI@sherwin.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Center

**Telephone number** : 0844 892 0111

#### Supplier

**Telephone number** : +39 051 770511

**Hours of operation** : Emergency contact available 24 hours a day

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Acute Tox. 4, H332  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Resp. Sens. 1, H334  
Skin Sens. 1, H317  
Repr. 2, H361d (Unborn child)  
STOT SE 3, H336 (Narcotic effects)  
STOT RE 2, H373

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : F; R11  
Repr. Cat. 3; R63  
Xn; R20, R48/20  
Xi; R36/38  
R42/43

PU HARDENER

TH0801/00

## SECTION 2: Hazards identification

**Physical/chemical hazards** : Highly flammable.

**Human health hazards** : Possible risk of harm to the unborn child. Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Irritating to eyes and skin. May cause sensitization by inhalation and skin contact.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : Highly flammable liquid and vapor. Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of damaging the unborn child. May cause drowsiness and dizziness. May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

**Prevention** :

Obtain special instructions before use. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Do not breathe vapor.

**Response** :

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

**Storage** :

Keep cool.

**Disposal** :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Hazardous ingredients

n-Butyl Acetate  
Methyl Ethyl Ketone  
Toluene  
Toluene Diisocyanate Polymer  
Urethane Polymer  
Toluene-2,4-diisocyanate (max.)  
Toluene-2,6-diisocyanate (max.)

### Supplemental label elements

Contains isocyanates. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. FOR INDUSTRIAL USE ONLY

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

### Special packaging requirements

Not applicable.

### Biocidal products regulation

### 2.3 Other hazards

PU HARDENER

TH0801/00

**SECTION 2: Hazards identification**

**Other hazards which do not result in classification** : None known.

**SECTION 3: Composition/information on ingredients****3.2 Mixture**

:

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
n-Butyl Acetate	REACH #: 01-2119485493-29 EC: 204-658-1  CAS: 123-86-4 Index: 607-025-00-1	>=25 - <35	R10  R66, R67	Flam. Liq. 3, H226  STOT SE 3, H336 (Narcotic effects)	[1] [2]
Methyl Ethyl Ketone	REACH #: 01-2119457290-43 EC: 201-159-0 CAS: 78-93-3  Index: 606-002-00-3	>=25 - <35	F; R11  Xi; R36 R66, R67	Flam. Liq. 2, H225  Eye Irrit. 2, H319 STOT SE 3, H336 (Narcotic effects)	[1] [2]
Toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3  Index: 601-021-00-3	>=20 - <25	F; R11  Repr. Cat. 3; R63 Xn; R48/20, R65  Xi; R38  R67	Flam. Liq. 2, H225  Skin Irrit. 2, H315 Repr. 2, H361d (Unborn child)  STOT SE 3, H336 (Narcotic effects) STOT RE 2, H373 Asp. Tox. 1, H304 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1] [2]
Toluene Diisocyanate Polymer Urethane Polymer	CAS: 9017-01-0  EC: 500-120-8 CAS: 53317-61-6	>=10 - <20	Xi; R36 R43	[1]	
Ethyl Acetate	REACH #: 01-2119475103-46 EC: 205-500-4 CAS: 141-78-6  Index: 607-022-00-5	>=1 - <5	Xi; R36 R66, R67	Eye Irrit. 2, H319 STOT SE 3, H336 (Narcotic effects)	[1] [2]
Toluene-2, 4-diisocyanate (max.)	REACH #: 01-2119486974-18 EC: 209-544-5 CAS: 584-84-9 Index: 615-006-00-4	>=0.1 - <0.25	Carc. Cat. 3; R40  T+; R26 Xi; R36/37/38 R42/43 R52/53	Acute Tox. 1, H330  Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 (Respiratory tract irritation) Aquatic Chronic 3, H412	[1] [2]
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

PU HARDENER

TH0801/00

## SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General

- : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

#### Eye contact

- : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

#### Inhalation

- : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

#### Skin contact

- : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

#### Ingestion

- : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Protection of first-aiders

- : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Repeated or prolonged contact with irritants may cause dermatitis.

Contains Toluene Diisocyanate Polymer, Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylenetrimethanol, 4-methyl-m-phenylene diisocyanate. May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to physician

- : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

#### Specific treatments

- : No specific treatment.

See toxicological information (Section 11)

PU HARDENER

TH0801/00

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, carbon dioxide, powders

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13).

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.**

**Examination of lung function should be carried out on a regular basis on persons spraying this mixture.**

### 7.1 Precautions for safe handling

- : Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Care should be taken when re-opening partly-used containers. Precautions should be taken to minimize exposure to atmospheric humidity or water. CO<sub>2</sub> will be formed, which, in closed containers, could result in pressurization. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

**Information on fire and explosion protection**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorized access.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilled product.

### Seveso II Directive - Reporting thresholds (in tonnes)

#### Named substances

Name	Notification and MAPP threshold	Safety report threshold
Toluene diisocyanate	10	100
Toluene diisocyanate	10	100

PU HARDENER

TH0801/00

**SECTION 7: Handling and storage****Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5000	50000
C7b: Highly flammable (R11)	5000	50000

**7.3 Specific end use(s)****Recommendations** : Not available.**Industrial sector specific solutions** : Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.**

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
n-Butyl Acetate	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 966 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m <sup>3</sup> 8 hours. TWA: 150 ppm 8 hours.
Methyl Ethyl Ketone	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> STEL: 899 mg/m <sup>3</sup> 15 minutes. STEL: 300 ppm 15 minutes. TWA: 600 mg/m <sup>3</sup> 8 hours. TWA: 200 ppm 8 hours.
Toluene	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> STEL: 384 mg/m <sup>3</sup> 15 minutes. TWA: 191 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.
Ethyl Acetate	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.
Toluene-2,4-diisocyanate (max.)	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Skin sensitizer.</b> STEL: 0.07 mg/m <sup>3</sup> , (as NCO) 15 minutes. TWA: 0.02 mg/m <sup>3</sup> , (as NCO) 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures

PU HARDENER

TH0801/00

## SECTION 8: Exposure controls/personal protection

for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

- Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

### DNELs/DMELs

No DNELs/DMELs available.

### PNECs

No PNECs available.

#### **8.2 Exposure controls**

**Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this product is used.**

**Examination of lung function should be carried out on a regular basis on persons spraying this mixture.**

#### **Appropriate engineering controls**

- Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn. (See Occupational exposure controls.)
- Users are advised to consider national Occupational Exposure Limits or other equivalent values.

### Individual protection measures

#### **Hygiene measures**

- Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

- Use safety eyewear designed to protect against splash of liquids.

#### **Skin protection**

#### **Hand protection**

#### **Gloves**

- Wear suitable gloves tested to EN374.
- Short Term Exposure less than 30 minutes Continuous use LDPE gloves, 30 microns or Butyl gloves 0.7mm  
Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Lamine gloves > 8 hours (breakthrough time).  
There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.  
The breakthrough time must be greater than the end use time of the product.  
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.  
Gloves should be replaced regularly and if there is any sign of damage to the glove material.  
Always ensure that gloves are free from defects and that they are stored and used correctly.  
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.  
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.  
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

#### **Body protection**

- Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.

PU HARDENER

TH0801/00

## SECTION 8: Exposure controls/personal protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.**

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Color** : Not available.

**Odor** : Characteristic.

**Odor threshold** : Not available.

**pH** : Testing not technically possible.

**Melting point/freezing point** : Not Available (Not Tested).

**Initial boiling point and boiling range** : 72°C

**Flash point** : Closed cup: -5°C [Pensky-Martens Closed Cup]

**Evaporation rate** : 5.6 (butyl acetate = 1)

**Flammability (solid, gas)** : Not Available (Not Tested).

**Burning time** : Not Available (Not Tested).

**Burning rate** : Not Available (Not Tested).

**Upper/lower flammability or explosive limits** : Lower: 1%  
Upper: 10.7%

**Vapor pressure** : 1.6 kPa [at 20°C]

**Vapor density** : 2.48 [Air = 1]

**Relative density** : 0.93

**Solubility(ies)** : Not Available (Not Tested).

**Solubility in water** : Not Available (Not Tested).

**Partition coefficient: n-octanol/water** : Not Available (Not Tested).

**Auto-ignition temperature** : Not Available (Not Tested).

**Decomposition temperature** : Not Available (Not Tested).

**Viscosity** : Kinematic (room temperature): <0.07 cm<sup>2</sup>/s  
Kinematic (40°C): >0.205 cm<sup>2</sup>/s

#### **Explosive properties**

PU HARDENER

TH0801/00

## SECTION 9: Physical and chemical properties

**Oxidizing properties** : Under normal conditions of storage and use, hazardous reactions will not occur.

### 9.2 Other information

**Heat of combustion** : 0.00003025 kJ/g

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions** : The product reacts slowly with water, resulting in the production of carbon dioxide. In closed containers, pressure buildup could result in distortion, expansion and, in extreme cases, bursting of the container.

**10.4 Conditions to avoid** : In a fire, hazardous decomposition products may be produced.

**10.5 Incompatible materials** : Keep away from: oxidizing agents, strong alkalis, strong acids, amines, alcohols, water. Uncontrolled exothermic reactions occur with amines and alcohols.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.**

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Repeated or prolonged contact with irritants may cause dermatitis.

Contains Toluene Diisocyanate Polymer, Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylenetrimethanol, 4-methyl-m-phenylene diisocyanate. May produce an allergic reaction.

### Acute toxicity

PU HARDENER

TH0801/00

**SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
n-Butyl Acetate	LC50 Inhalation Gas. LD50 Dermal	Rat Rabbit	390 ppm >17600 mg/kg	4 hours -
Methyl Ethyl Ketone	LD50 Oral	Rat	10768 mg/kg	-
	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 Oral	Rat	2737 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	636 mg/kg	-
	LD50 Oral	Rat	5620 mg/kg	-
Ethyl Acetate	LC50 Inhalation Gas.	Rat	14 ppm	4 hours
Toluene-2,4-diisocyanate (max.)	LD50 Oral	Rat	5800 mg/kg	-

**Acute toxicity estimates**

Route	ATE value
Inhalation (gases)	7871.2 ppm

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-Butyl Acetate	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Methyl Ethyl Ketone	Skin - Mild irritant	Rabbit	-	24 hours 14 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
Toluene-2,4-diisocyanate (max.)	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Severe irritant	Rabbit	-	500 milligrams	-

**Conclusion/Summary** : Not available.**Sensitization**

No data available

**Conclusion/Summary** : Not available.**Mutagenicity**

No data available

**Carcinogenicity**

No data available

PU HARDENER

TH0801/00

**SECTION 11: Toxicological information****Reproductive toxicity**

No data available

**Teratogenicity**

No data available

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
n-Butyl Acetate	Category 3	Not applicable.	Narcotic effects
Methyl Ethyl Ketone	Category 3	Not applicable.	Narcotic effects
Toluene	Category 3	Not applicable.	Narcotic effects
Ethyl Acetate	Category 3	Not applicable.	Narcotic effects
Toluene-2,4-diisocyanate (max.)	Category 3	Not applicable.	Respiratory tract irritation

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Toluene	Category 2	Not determined	Not determined

**Aspiration hazard**

Product/ingredient name	Result
Toluene	ASPIRATION HAZARD - Category 1

***Other information*** : Not available.**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
n-Butyl Acetate	Acute LC50 32000 µg/l Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
Methyl Ethyl Ketone	Acute LC50 18000 µg/l Fresh water Acute EC50 >500000 µg/l Marine water Acute EC50 5091000 µg/l Fresh water	Fish - Pimephales promelas Algae - Skeletonema costatum Daphnia - Daphnia magna - Larvae	96 hours 96 hours 48 hours
Toluene	Acute LC50 3220000 µg/l Fresh water Acute EC50 12500 µg/l Fresh water  Acute EC50 11600 µg/l Fresh water  Acute EC50 6000 µg/l Fresh water  Acute LC50 5500 µg/l Fresh water	Fish - Pimephales promelas Algae - Pseudokirchneriella subcapitata Crustaceans - Gammarus pseudolimnaeus - Adult Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) Fish - Oncorhynchus kisutch - Fry	96 hours 72 hours  48 hours 48 hours 96 hours
Ethyl Acetate	Chronic NOEC 1000 µg/l Fresh water Acute EC50 2500000 µg/l Fresh water Acute LC50 750000 µg/l Fresh water Acute LC50 154000 µg/l Fresh water Acute LC50 212500 µg/l Fresh water Chronic NOEC 2400 µg/l Fresh water	Daphnia - Daphnia magna Algae - Selenastrum sp. Crustaceans - Gammarus pulex Daphnia - Daphnia cucullata Fish - Heteropneustes fossilis Daphnia - Daphnia magna	21 days 96 hours 48 hours 48 hours 96 hours 21 days

PU HARDENER

TH0801/00

**SECTION 12: Ecological information**

Toluene-2,4-diisocyanate (max.)	Chronic NOEC 75.6 mg/l Fresh water Acute LC50 164500 µg/l Fresh water	Fish - Pimephales promelas - Embryo Fish - Pimephales promelas	32 days 96 hours
------------------------------------	--	---	---------------------

**12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-Butyl Acetate	-	-	Readily
Methyl Ethyl Ketone	-	-	Readily
Toluene	-	-	Readily
Ethyl Acetate	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Toluene	-	90	low
Ethyl Acetate	-	30	low

**12.4 Mobility in soil****Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment****PBT** : Not applicable.**vPvB** : Not applicable.**12.6 Other adverse effects** : No known significant effects or critical hazards.

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.**European waste catalogue (EWC)** : waste isocyanates 08 05 01\*

PU HARDENER

TH0801/00

**SECTION 13: Disposal considerations**

**Disposal considerations** : Do not allow to enter drains or watercourses. Residues in empty containers should be neutralized with a decontaminant (see section 6). Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**European waste catalogue (EWC)** : packaging containing residues of or contaminated by dangerous substances 15 01 10\*

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
<b>14.1 UN number</b>	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
<b>14.3 Transport Hazard Class(es)/Label(s)</b>	3 	3 	3 
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	No.	No.	No.
<b>Additional information</b>	<u>Special provisions</u> 640 (C)  <u>Tunnel code</u> D/E	<u>Emergency schedules (EmS)</u> F-E, S-E	<u>Special provisions</u> Not Applicable

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

: Not available.

PU HARDENER

TH0801/00

**SECTION 14: Transport information**

*Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.*

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorization****Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions** : Not applicable.

*on the manufacture,  
placing on the market  
and use of certain  
dangerous substances,  
mixtures and articles*

**Other EU regulations**

**European Directive 2004/42/EC** : Exclusively for uses non-regulated by directive 2004/42/EC

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
Toluene	-	-	Repr. 2, H361d (Unborn child)	-
Toluene-2,4-diisocyanate (max.)	Carc. 2, H351	-	-	-

**Seveso II Directive**

This product is controlled under the Seveso II Directive.

**Named substances**

Name
Toluene-2,6-diisocyanate (max.)
Toluene-2,4-diisocyanate (max.)

**Danger criteria**

Category
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b
C7b: Highly flammable (R11)

**National regulations**

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**International regulations**

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

PU HARDENER

TH0801/00

**SECTION 16: Other information**

 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms**

- : ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

**Key literature references and sources for data**

- : Regulation (EC) No. 1272/2008 [CLP]
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- DPD = Dangerous Preparations Directive [1999/45/EC]
- DSD = Dangerous Substances Directive [67/548/EEC]
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010
- Directive 96/82/EC, and relative amendments & additions
- Directive 2008/98/EC, and relative amendments & additions
- Directive 2000/39/EC, and relative amendments & additions
- CEPE Guidelines

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Classification	Justification
Flam. Liq. 2, H225	On basis of test data
Acute Tox. 4, H332	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 2, H361d (Unborn child)	Calculation method
STOT SE 3, H336 (Narcotic effects)	Calculation method
STOT RE 2, H373	Calculation method

**Full text of abbreviated H statements**

- : H225      Highly flammable liquid and vapor.
- H226      Flammable liquid and vapor.
- H304      May be fatal if swallowed and enters airways.
- H315      Causes skin irritation.
- H317      May cause an allergic skin reaction.
- H319      Causes serious eye irritation.
- H330      Fatal if inhaled.
- H332      Harmful if inhaled.  
(inhalation)
- H334      May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335      May cause respiratory irritation. (Respiratory tract irritation)  
(Respiratory tract irritation)
- H336 (Narcotic effects)      May cause drowsiness and dizziness. (Narcotic effects)
- H351      Suspected of causing cancer.
- H361d (Unborn child)      Suspected of damaging the unborn child.
- H373      May cause damage to organs through prolonged or repeated exposure.
- H412      Harmful to aquatic life with long lasting effects.

PU HARDENER

TH0801/00

**SECTION 16: Other information**

<b>Full text of classifications [CLP/GHS]</b>	: <table> <tr><td>Acute Tox. 1, H330</td><td>ACUTE TOXICITY (inhalation) - Category 1</td></tr> <tr><td>Acute Tox. 4, H332</td><td>ACUTE TOXICITY (inhalation) - Category 4</td></tr> <tr><td>Aquatic Chronic 3, H412</td><td>AQUATIC HAZARD (LONG-TERM) - Category 3</td></tr> <tr><td>Asp. Tox. 1, H304</td><td>ASPIRATION HAZARD - Category 1</td></tr> <tr><td>Carc. 2, H351</td><td>CARCINOGENICITY - Category 2</td></tr> <tr><td>Eye Irrit. 2, H319</td><td>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2</td></tr> <tr><td>Flam. Liq. 2, H225</td><td>FLAMMABLE LIQUIDS - Category 2</td></tr> <tr><td>Flam. Liq. 3, H226</td><td>FLAMMABLE LIQUIDS - Category 3</td></tr> <tr><td>Repr. 2, H361d (Unborn child)</td><td>TOXIC TO REPRODUCTION (Unborn child) - Category 2</td></tr> <tr><td>Resp. Sens. 1, H334</td><td>RESPIRATORY SENSITIZATION - Category 1</td></tr> <tr><td>Skin Irrit. 2, H315</td><td>SKIN CORROSION/IRRITATION - Category 2</td></tr> <tr><td>Skin Sens. 1, H317</td><td>SKIN SENSITIZATION - Category 1</td></tr> <tr><td>STOT RE 2, H373</td><td>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2</td></tr> <tr><td>STOT SE 3, H335 (Respiratory tract irritation)</td><td>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3</td></tr> <tr><td>STOT SE 3, H336 (Narcotic effects)</td><td>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3</td></tr> </table>	Acute Tox. 1, H330	ACUTE TOXICITY (inhalation) - Category 1	Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4	Aquatic Chronic 3, H412	AQUATIC HAZARD (LONG-TERM) - Category 3	Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1	Carc. 2, H351	CARCINOGENICITY - Category 2	Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2	Flam. Liq. 2, H225	FLAMMABLE LIQUIDS - Category 2	Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3	Repr. 2, H361d (Unborn child)	TOXIC TO REPRODUCTION (Unborn child) - Category 2	Resp. Sens. 1, H334	RESPIRATORY SENSITIZATION - Category 1	Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2	Skin Sens. 1, H317	SKIN SENSITIZATION - Category 1	STOT RE 2, H373	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	STOT SE 3, H335 (Respiratory tract irritation)	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	STOT SE 3, H336 (Narcotic effects)	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Acute Tox. 1, H330	ACUTE TOXICITY (inhalation) - Category 1																														
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4																														
Aquatic Chronic 3, H412	AQUATIC HAZARD (LONG-TERM) - Category 3																														
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1																														
Carc. 2, H351	CARCINOGENICITY - Category 2																														
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2																														
Flam. Liq. 2, H225	FLAMMABLE LIQUIDS - Category 2																														
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3																														
Repr. 2, H361d (Unborn child)	TOXIC TO REPRODUCTION (Unborn child) - Category 2																														
Resp. Sens. 1, H334	RESPIRATORY SENSITIZATION - Category 1																														
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2																														
Skin Sens. 1, H317	SKIN SENSITIZATION - Category 1																														
STOT RE 2, H373	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2																														
STOT SE 3, H335 (Respiratory tract irritation)	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3																														
STOT SE 3, H336 (Narcotic effects)	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3																														
<b>Full text of abbreviated R phrases</b>	: <p>R11- Highly flammable.        R10- Flammable.        R40- Limited evidence of a carcinogenic effect.        R63- Possible risk of harm to the unborn child.        R26- Very toxic by inhalation.        R20- Harmful by inhalation.        R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.        R65- Harmful: may cause lung damage if swallowed.        R36- Irritating to eyes.        R38- Irritating to skin.        R36/38- Irritating to eyes and skin.        R36/37/38- Irritating to eyes, respiratory system and skin.        R43- May cause sensitization by skin contact.        R42/43- May cause sensitization by inhalation and skin contact.        R66- Repeated exposure may cause skin dryness or cracking.        R67- Vapors may cause drowsiness and dizziness.        R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p>																														
<b>Full text of classifications [DSD/DPD]</b>	: <p>F - Highly flammable        Carc. Cat. 3 - Carcinogen category 3        Repr. Cat. 3 - Toxic to reproduction category 3        T+ - Very toxic        Xn - Harmful        Xi - Irritant</p>																														
<b>Date of printing</b>	: <p>17, Apr, 2015.</p>																														
<b>Date of issue/ Date of revision</b>	: <p>17, Apr, 2015.</p>																														
<b>Date of previous issue</b>	: <p>No previous validation.        If there is no previous validation date please contact your supplier for more information.</p>																														
<b>Version</b>	: <p>1</p>																														
<b>Notice to reader</b>																															

PU HARDENER

TH0801/00

## SECTION 16: Other information

*It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.*